

# CO-150

Premium synthetic blend oven conveyor chain oil



## Your benefits at a glance

The formulation of CO-150 incorporates an additive system that provides the following benefits to tender chains:

- Excellent anti-wear properties to prolong chain life
- A viscosity for spraying the lubricant onto the chain
- High-temperature capabilities
- Cleaning of the chain as it operates
- Anti-oxidants to reduce gumming and thickening
- Water insoluble
- Adheres to the chain
- Penetration

## Your requirements - our solution

CO-150 chain oil is a unique blend of the highest quality petroleum oil available today and selected synthetic base stocks. This blend contains an additive system formulated to meet the demanding requirements for a tender chain lubricant.

## Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	CO-150
Article number	340015
Fire point	280 °C
Kinematic viscosity, 100°C	14.8 mm <sup>2</sup> /s
Kinematic viscosity, 40°C	127 mm <sup>2</sup> /s
Viscosity index	118
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346, based on standard	-39 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

## Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /  
9010 County Road 2120, Tyler, TX 75707 /  
Phone: +1 800 749 5823 / [www.klsummit.com](http://www.klsummit.com)

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.