Product information

DSL®-10

Synthetic chain lubricants

Your benefits at a glance

This blend provides for the following benefits to chains:

- Excellent anti-wear properties to prolong chain life
- Light viscosity for spraying the lubricant onto the chain
- High temperature capabilities
- Cleaning of the chain as it operates
- Anti-oxidants to reduce gumming and thickening
- Water insoluble
- Penetration

DSL®-10 chain oil is a unique blend of diester base stocks and an additive system designed to meet the demanding requirements for a low viscosity, thermally stable chain oil.

DSL®-10 is also suitable for general purpose high temperature applications requiring a low viscosity lubricant.

Application

Chains

Material safety data sheets

Material safety data sheets can be requested via our website https://www.klsummit.com. You may also obtain them through your contact person at Summit Lubrication.

Your requirements - our solution

Characteristics	DSL-10
Article number	340021
Density, 20°C	approx. 0.852 g/cm³
Fire point, Cleveland open cup	≥ 175 °C
Flash point, ASTM D92, Cleveland open cup	≥ 155 °C
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 100°C	approx. 2.85 mm²/s
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 40°C	approx. 10.7 mm²/s
Viscosity index, ASTM D2270	approx. 116
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346	approx. -77 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

a brand of KLÜBER LUBRICATION

Product information

DSL®-10

Synthetic chain lubricants

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.