

HyPar HVI Series

Premium hydraulic oil



Your benefits at a glance

- Protects against rust, wear and sludge
- Operates over a wide temperature range

Your requirements - our solution

Summit HyPar HVI Series ashless hydraulic oils are formulated to meet the requirements of all types of hydraulic systems. They are rust and oxidation inhibited to protect against rust, wear and the formation of sludge. These oils are compatible with seal materials normally used in hydraulic systems.

Summit HyPar HVI ashless hydraulic oils contain the additives necessary to meet the requirements for Denison HF-O, Vickers industrial and mobile applications and Cincinnati Milacron P-68, P-69 and P-70 specifications.

HyPar 55-HVI is blended at an optimum viscosity for plastic injection molding machines and other similar applications. The high viscosity index of HyPar 32-HVI allows for operation over a wide temperature range and assures fluid flow at lower temperatures.

Summit HyPar 55-HVI is a zinc-free ashless hydraulic oil formulated to meet the requirements of all types of hydraulic systems. It is blended at an optimum viscosity for plastic injection molding machines and other similar applications. HyPar 55-HVI is rust and oxidation inhibited to protect against rust, wear and formation of sludge. It is compatible with seal materials normally used in hydraulic systems.

Summit HyPar 55-HVI hydraulic oil contains additives necessary to meet the requirements for Denison HF-O, Vickers industrial and mobile applications and Cincinnati Milacron P-68, P-69 and P-70 specifications.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	HYPAR-32HVI	HYPAR-55HVI
Article number	340452	340537
Density	0.862 g/cm ³	0.86 g/cm ³
Fire point	218 °C	271 °C
Flash point	175 °C	215 °C
Kinematic viscosity, 100°C	8.3 mm ² /s	9.0 mm ² /s
Kinematic viscosity, 40°C	32.7 mm ² /s	55.8 mm ² /s
Viscosity index	244	141
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346, based on standard	-43 °C	-42 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	0 months

HyPar HVI Series

Premium hydraulic oil



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsupport.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.