

PGS-2-22X

Synthetic natural gas compressor



Your benefits at a glance

- Resistant to viscosity thinning
- Versatile with various types of rotary compressors
- Can be used as a mechanical seal oil

Your requirements - our solution

PGS-2-22X is a specialized polyglycol (PAG) based lubricant for use in heavy hydrocarbon gas compressor applications where other lubricants, including synthetics, suffer from excessive viscosity thinning. The type of PAG used in PGS-2-22X is even more resistant to this thinning effect than other PAGs commonly used in these applications. It may be used in various types of rotary compressors where the gas being compressed consists of high BTU hydrocarbons. PGS-2-22X is also formulated for use as a mechanical seal oil when PAGs of similar chemistry but higher viscosity, such as PGS-2, PGS-2-68 and PGS-3, are being used as

the main compressor lubricant. It does not contain additives that would contribute to fouling of the seal face in high temperature applications.

PGS-2-22X is not compatible with petroleum, PAO, ester and some PAG based lubricants. Care should be taken when two different lubricants may be mixed or come into contact with one another. Please contact Summit if you have any concerns regarding compatibility.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

| Characteristics | PGS-2-22X |
|--|-------------------------|
| Article number | 340438 |
| Density | 1.117 g/cm ³ |
| Flash point | 173 °C |
| Kinematic viscosity, 100°C | 4.3 mm ² /s |
| Kinematic viscosity, 40°C | 23.0 mm ² /s |
| Viscosity index | 83 |
| Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346, based on standard | -61 °C |
| Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx. | 60 months |

PGS-2-22X

Synthetic natural gas compressor



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsupport.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.