- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

SECTION 1. IDENTIFICATION

Product name : DSL-150

Article-No. : 340028

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Klüber Lubrication NA LP

9010 County Road 2120

Tyler, Texas 75707

USA

Phone: +1 903 534-8021 Fax: +1 903 581-4376

32 Industrial Drive Londonderry, NH 03053

USA

Phone: +1 603 647-4104 Fax: +1 603 647-4106

E-mail address of person

responsible for the SDS

: mcm@us.kluber.com

Material Compliance Management

Emergency telephone

number

: +1-517-545-7070 NCEC

Recommended use of the chemical and restrictions on use

Recommended use : Lubricating oil

Restrictions on use : Restricted to professional users.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms

Signal word : Warning

- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

Hazard statements : Suspected of damaging fertility.

Precautionary statements : **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Response:

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : ester oil

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	White mineral oil (petroleum)	8042-47-5	Trade secret** (>= 1 - < 5 *)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Lubricating oils (petroleum), C15-30, hydrotreated neutral oilbased; Baseoil — unspecified	72623-86-0	Trade secret** (>= 1 - < 5 *)
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpenten e	68411-46-1	Trade secret** (>= 1 - < 5 *)



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

SECTION 4. FIRST AID MEASURES

If inhaled : Obtain medical attention.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

In case of contact, immediately flush skin with plenty of water.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed: Move the victim to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No information available.

None known.

Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion : Carbon oxides

^{*} Actual concentration or concentration range is withheld as a trade secret

^{**} See Section 15 for HMIRA information.

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

products Nitrogen oxides (NOx)

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.
Use personal protective equipment.

Ensure adequate ventilation.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions :

Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid inhalation of vapour or mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest. Do not repack.

Do not re-use empty containers.

These safety instructions also apply to empty packaging which

may still contain product residues. Keep container closed when not in use.

Conditions for safe storage

Store in original container.

Keep container closed when not in use.

- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

Keep in a dry, cool and well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with the particular national regulations.

Keep in properly labelled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL (2009-04-30)
		STEL (Mist)	10 mg/m3	CA AB OEL (2009-04-30)
		TWAEV (Mist)	5 mg/m3	CA QC OEL (2012-11-28)
		STEV (Mist)	10 mg/m3	CA QC OEL (2012-11-28)
		TWA (Mist)	1 mg/m3	CA BC OEL (2012-04-20)
		TWA (Mist)	1 mg/m3	CA BC OEL (2021-01-04)
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL (2009-04-30)
		STEL (Mist)	10 mg/m3	CA AB OEL (2009-04-30)
		TWAEV (Mist)	5 mg/m3	CA QC OEL (2012-11-28)
		STEV (Mist)	10 mg/m3	CA QC OEL (2012-11-28)
		TWA (Mist)	1 mg/m3	CA BC OEL (2021-01-04)
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)

Engineering measures

Handle only in a place equipped with local exhaust (or other appropriate exhaust).



- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

Personal protective equipment

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type A-P

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : No data available

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

Flash point : 263 °C

Method: ASTM D 92

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : < 0.001 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.944 (20 °C)

Reference substance: Water The value is calculated

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 150 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : No conditions to be specially mentioned.

Incompatible materials : No materials to be especially mentioned.

Hazardous decomposition

products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

Components:

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

White mineral oil (petroleum):

Germ cell mutagenicity - : Tests on bacterial or mammalian cell cultures did not show

Assessment mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

Components:

White mineral oil (petroleum):

Carcinogenicity - Assessment No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

Remarks: No data available

Components:

White mineral oil (petroleum):

Reproductive toxicity -

- Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Reproductive toxicity -

: - Fertility -

Assessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

STOT - single exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

Aspiration toxicity

Product:

This information is not available.

Components:

White mineral oil (petroleum):

May be fatal if swallowed and enters airways.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 28 d

Remarks: The value is given based on a SAR/AAR approach

using OECD Toolbox, DEREK, VEGA QSAR models

(CAESAR models), etc.

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): >= 1,000 mg/l

Exposure time: 21 d

Remarks: The value is given based on a SAR/AAR approach

using OECD Toolbox, DEREK, VEGA QSAR models

(CAESAR models), etc.

Toxicity to microorganisms : LC50 (Bacteria): > 1,000 mg/l

Exposure time: 40 h

Test Type: Growth inhibition

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

Components:

White mineral oil (petroleum):

Biodegradability : Biodegradation: 31 %

Exposure time: 28 d

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

GLP: yes

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 1 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

- CA



DSL-150

 Version
 Revision Date:
 Date of last issue: 2021-09-02
 Print Date:

 2.0
 2022-10-03
 Date of first issue: 2021-09-02
 2022-10-03

Components:

White mineral oil (petroleum):

Partition coefficient: n-

octanol/water

log Pow: > 6

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Partition coefficient: n-

octanol/water

log Pow: > 5

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

Harmful to aquatic life with long lasting effects.

Components:

White mineral oil (petroleum):

Results of PBT and vPvB

assessment

This substance is not considered to be persistent,

bioaccumulating and toxic (PBT).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

NPRI Components : Canadian National Pollutant Release Inventory (NPRI): No

component is listed on NPRI.

Canadian lists

No substances are subject to a Significant New Activity Notification.

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA, ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and

safety, Schedule 1, Part 1: Permissible exposure values for

airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2022-10-03 Date format : mm/dd/yyyy

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the

- CA



DSL-150

VersionRevision Date:Date of last issue: 2021-09-02Print Date:2.02022-10-03Date of first issue: 2021-09-022022-10-03

product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.