Seamer Oil-150P

Seamer gear oil

Your benefits at a glance

- Provides excellent wear, EP, and corrosion properties
- Passes all 12 stages of the FZG Gear Test
- Produced under the strictest hygienic guidelines for food grade lubricant production

Your requirements - our solution

Seamer Oil-150P is specially formulated to lubricate the gear systems found in "once through" designed can closers used in food canning operations. This machine design allows the oil to cascade through the gears, lubricating as it goes, until it is discharged into the sanitary drain system from the bottom of the machine. Seamer Oil-150P is blended using the highest quality base stocks and utilizes an additive package that provides excellent wear, EP, and corrosion properties. This superior formulation passes all 12 stages of the FZG Gear Test. Tested extensively, Seamer Oil-150P has demonstrated exceptional results when used in this application.

Manufactured in Summit´s ISO 21469 Certified facility, this product is produced under the strictest hygienic guidelines for food grade lubricant production. Seamer Oil-150P is NSF H1 approved for use where there is a possibility of incidental contact with the food being processed.

Material safety data sheets

Material safety data sheets can be requested via our website https://www.klsummit.com. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	SEAMER OIL 150P
Article number	340325
Density, 20°C	approx. 0.867 g/cm³
Flash point, ASTM D92, Cleveland open cup	≥ 230 °C
ISO viscosity grade, DIN ISO 3448, ISO VG	150
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 100°C	approx. 15.0 mm²/s
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 40°C	approx. 150 mm²/s
Viscosity index, ASTM D2270	approx. 99
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346	approx. -22 °C
FZG scuffing test, DIN ISO 14635-1, A / 8.3 / 90, failure load stage	12+
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

a brand of KLÜBER LUBRICATION

Product information

Seamer Oil-150P

Seamer gear oil

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.