

Seamer Oil-150S

Seamer gear oil



Your benefits at a glance

- Protects the gearing and other moving parts of the machine
- Suspend contaminants for filtering and removal of water
- Fortified with oxidation inhibitors, corrosion inhibitors and antiwear additives
- Holds water, juice, syrups and other contaminants in suspension allowing for easy removal

Your requirements - our solution

Summit Seamer Oil 150 S is designed to lubricate can seaming equipment which reclaims the used oil. This specialized application requires a product that protects the gearing and other moving parts of the machine. The lubricant must also suspend contaminants for filtering and removal of water. Fortified with oxidation inhibitors, corrosion inhibitors and antiwear additives, Seamer Oil 150 S protects the moving parts of the machine. In addition, this formula

holds water, juice, syrups and other contaminants in suspension allowing for easy removal.

Produced in Summit's ISO 21469 Certified manufacturing plant, Seamer Oil 150 S meets USDA 1998 (H1) guidelines (lubricants for incidental food contact).

Application notes

Note: For canning systems utilizing a "total loss system" or "once through system", use Summit Seamer Oil 150 P

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	SEAMER OIL 150S
Article number	340349
Density	0.851 g/cm ³
Fire point	302 °C
Flash point	260 °C
Kinematic viscosity, 100°C	19.2 mm ² /s
Kinematic viscosity, 40°C	154.7 mm ² /s
Viscosity index	142
Copper corrosion	1 - - corrosion degree
Steel corrosion	passed
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346, based on standard	-45 °C
Four-ball tester: wear characteristics	0.32 mm
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Seamer Oil-150S

Seamer gear oil



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsupport.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.