

# Syngear® PG Series

Synthetic gears/bearings



## Your benefits at a glance

- Better wear protection
- Thermal and oxidation stability
- Reduced sludge and deposit formation

## Your requirements - our solution

Summit Syngear PG Series synthetic lubricants are polyglycol-based products for use in enclosed gear, bearings, and compressors where conditions demand the unique properties of these fluids. Better wear protection, thermal stability, and reduced sludge and deposit formation insure enhanced performance when compared to petroleum-based lubricants.

## Application notes

Syngear PG Series lubricants are incompatible with petroleum oils. Care should be taken to make sure the two types of fluids are not mixed.

## Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	SYNGEAR PG-220	SYNGEAR PG-320	SYNGEAR PG-460	SYNGEAR PG-680
Article number	340164	340165	340166	340167
Density	1.041 g/cm <sup>3</sup>	1.043 g/cm <sup>3</sup>	1.045 g/cm <sup>3</sup>	1.045 g/cm <sup>3</sup>
Flash point	266 °C	271 °C	277 °C	274 °C
Kinematic viscosity, 100°C	42.9 mm <sup>2</sup> /s	55.2 mm <sup>2</sup> /s	80.7 mm <sup>2</sup> /s	113.4 mm <sup>2</sup> /s
Kinematic viscosity, 40°C	221.9 mm <sup>2</sup> /s	307.4 mm <sup>2</sup> /s	433.3 mm <sup>2</sup> /s	653.8 mm <sup>2</sup> /s
Viscosity index	244	247	259	273
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346, based on standard	-43 °C	-41 °C	-40 °C	-42 °C
FZG scuffing test	12+	12+	12+	12+
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months	36 months	36 months

Characteristics	SYNGEAR PG-1000
Article number	340203
Density	1.0672 g/cm <sup>3</sup>
Flash point	274 °C
Kinematic viscosity, 100°C	162.0 mm <sup>2</sup> /s
Kinematic viscosity, 40°C	1000 mm <sup>2</sup> /s

# Syngear® PG Series

Synthetic gears/bearings



Characteristics	SYNGEAR PG-1000
Viscosity index	280
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346, based on standard	-42 °C
FZG scuffing test	12+
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

## Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /  
9010 County Road 2120, Tyler, TX 75707 /  
Phone: +1 800 749 5823 / [www.klsummit.com](http://www.klsummit.com)

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.