

Syngear® SH®-1000 Series

Synthetic gears/Heavy Duty



Your benefits at a glance

- Thermal and oxidation stability
- Protection against wear, rust, corrosion and foaming
- High viscosity index

Your requirements - our solution

Summit Syngear SH-1000 Series gear lubricants are formulated with synthetic base stocks and fortified with select additive systems to enhance their exceptional performance. The PAO base fluid used has outstanding oxidation and thermal stability, naturally high viscosity index and excellent low temperature pumpability and fluidity. The unique additive system used provides increased oxidation stability, extreme pressure properties, and maximum protection against wear, rust, corrosion and foaming.

In today's world of efficiency improvements, there has been much emphasis placed on reducing energy requirements for equipment used in plant operations. Summit Syngear synthetic gear lubricants have proven to reduce friction, thereby reducing the input power to operate the equipment or increasing the available power output. The reduction of fluid friction results in lower lubricant operating temperatures, prolonging the life of both the lubricant and the equipment. The additive system used in this product not only reduces frictional drag, but also protects gears against failures associated with heavy loading and meets the requirements of U.S. Steel 224 specification, AGMA 9005-D94 specification, DIN 51517 Part 3 CLP specification and API GL-4 Gear Service Category.

Application

Summit Syngear SH-1000 Series gear lubricants are recommended for use in all types of enclosed gearing as well as plain and rolling element bearings. These lubricants are ideal for heavily loaded low speed gears and bearings where boundary or elasto-hydrodynamic lubrication (EHL) conditions exist, such as in mine hoist gear reducers. They are particularly recommended for gearboxes which operate under excessively high temperatures where good quality conventional oils rapidly oxidize. Summit Syngear SH-1000 Series gear lubricants may also be used in certain open gear applications, but it is recommended that Summit lubrication engineers be consulted to select the most effective method of application. Summit Syngear SH-10032, SH-10046 and SH-10068 are also recommended for use in piston or gear-type pumps, especially where pressures exceed 1000 psi or when operating over a wide temperature range.

Application notes

Summit Syngear SH-1000 Series gear lubricants are compatible with the most seal materials, paints and plastics, including nitrile Buna N, neoprene, Viton®, Teflon®, polyethylene, polyurethane, ether, fluorocarbon, polyacrylate, polysulfide, ethylene acrylic, epoxy, plasticol, PVC, acrylic paint and lacquer.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	SYNGEAR SH-10032	SYNGEAR SH-10046	SYNGEAR SH-10068	SYNGEAR SH-1010
Article number	340124	340202	340125	340126
Density	0.838 g/cm ³	0.845 g/cm ³	0.85 g/cm ³	0.854 g/cm ³
Flash point	204 °C	204 °C	204 °C	204 °C
ISO viscosity grade	32	46	68	100
Kinematic viscosity, 100°C	5.8 mm ² /s	7.4 mm ² /s	9.9 mm ² /s	12.9 mm ² /s

Syngear® SH®-1000 Series

Synthetic gears/Heavy Duty



Kinematic viscosity, 40°C	31.0 mm ² /s	42.9 mm ² /s	67.1 mm ² /s	95.7 mm ² /s
Viscosity index	132	137	130	132
Copper corrosion	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree
Steel corrosion	passed	passed	passed	passed
Pour point	-50 °C	-40 °C	-42 °C	-41 °C
Four-ball tester: wear characteristics	0.50 mm	0.40 mm	0.30 mm	0.30 mm
Four-ball tester, welding load	200 kgf	200 kgf	200 kgf	200 kgf
FZG scuffing test	12+	12+	12+	12+
Timken test	60 lbs	60 lbs	65 lbs	65 lbs
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months	60 months	60 months

Characteristics	SYNGEAR SH-1015	SYNGEAR SH-1022	SYNGEAR SH-1032	SYNGEAR SH-1046
Article number	340453	340454	340455	340456
Density	0.865 g/cm ³	0.87 g/cm ³	0.87 g/cm ³	0.879 g/cm ³
Flash point	200 °C	200 °C	200 °C	200 °C
ISO viscosity grade	150	220	320	460
Kinematic viscosity, 100°C	18.2 mm ² /s	25.8 mm ² /s	33.4 mm ² /s	44.1 mm ² /s
Kinematic viscosity, 40°C	147 mm ² /s	229 mm ² /s	326 mm ² /s	485 mm ² /s
Viscosity index	141	144	145	144
Copper corrosion	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree
Steel corrosion	passed	passed	passed	passed
Pour point	-44 °C	-43 °C	-44 °C	-43 °C
Four-ball tester: wear characteristics	0.39 mm	0.34 mm	0.30 mm	0.30 mm
Four-ball tester, welding load	315 kgf	315 kgf	315 kgf	315 kgf
FZG scuffing test	12+	12+	12+	12+
Timken test	65 lbs	65 lbs	65 lbs	65 lbs
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months	60 months	60 months

Characteristics	SYNGEAR SH-1068	SYNGEAR SH-1100	SYNGEAR SH-1150
Article number	340457	340458	340253
Density	0.89 g/cm ³	0.89 g/cm ³	0.883 g/cm ³

Syngear® SH®-1000 Series

Synthetic gears/Heavy Duty



Characteristics	SYNGEAR SH-1068	SYNGEAR SH-1100	SYNGEAR SH-1150
Flash point	200 °C	200 °C	204 °C
ISO viscosity grade	680	1000	1500
Kinematic viscosity, 100°C	55.2 mm ² /s	70.8 mm ² /s	95.8 mm ² /s
Kinematic viscosity, 40°C	688 mm ² /s	959 mm ² /s	1513 mm ² /s
Viscosity index	141	122	143
Copper corrosion	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree
Steel corrosion	passed	passed	passed
Pour point	-37 °C	-34 °C	-27 °C
Four-ball tester: wear characteristics	0.30 mm	0.30 mm	0.30 mm
Four-ball tester, welding load	315 kgf	400 kgf	400 kgf
FZG scuffing test	12+	12+	12+
Timken test	65 lbs	65 lbs	65+ lbs
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months	60 months

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.